



► RIBS

	SUNDREAM	IIC	II	III	IV
DIMENSIONS (METERS - FEET/INCHES)					
Overall length	5 - 16'5"	5,3 - 17'5"	5,98 - 19'8"	7,3 - 23'12"	8,5 - 27'11"
Inside length	3,9 - 12'10"	3,68 - 12'1"	4,95 - 16'3"	5,02 - 16'6"	7,45 - 24'5"
Overall width	2,2 - 7'3"	2,24 - 7'4"	2,5 - 8'2"	3 - 9'10"	3 - 9'10"
Inside width	1,2 - 3'11"	1,2 - 3'11"	1,35 - 4'5"	1,85 - 6'1"	1,85 - 6'1"
Buoyancy tube diameter	0,5 - 1'8"	0,52 - 1'8"	0,575 - 1'11"	0,575 - 1'11"	0,6 - 1'12"
CAPACITY					
Passengers (ISO)	10	9	11 / 5 ⁶	15 / 8 ⁶	15 / 8 ⁶
Maximum payload ¹ (kg - lbs)	1150 - 2535,3	1115 - 2458,2	1550 - 3417,2 ⁶	1750 - 3858,1 ⁶	2130 - 4695,8 ⁶
	-	-	1100 - 2425,1 ⁶	1300 - 2866,0 ⁶	1605 - 3538,4 ⁶
Total weight (kg - lbs)	397 - 875,2	480 - 1058,2	690 - 1521,2	1400 - 3086,5	1600 - 3527,4
Airtight compartments	5	5	5	7	7
DESIGN CATEGORY					
European directive N° 94/25/CE	C	C	C / B	C / B	C / B
OUTBOARD DATA					
Shaft: ● Short ■ long ✕ Extralong * Ultralong ▲ Jet	■	■	✕	✕ ⁷	* ¹²
Minimum recommended power ² (Hp)	40	40	115	130	250
Minimum recommended power ² (kW)	30	30	86	96	188
Maximum recommended power ² (Hp)	60	75	150	250	300
Maximum recommended power ² (kW)	44	56	112	186	225
Maximum power allowed ³ (Hp)	80	115	150	250 ⁸	350 ¹⁰
Maximum power allowed ³ (kW)	59	86	112	186 ⁸	262 ¹⁰
Maximum weight of outboard ⁴ (kg - lbs)	180 - 396,8	195 - 429,9	240 - 529,1	300 - 661,4 ⁹	380 - 837,8 ¹¹
Maximum speed ⁵ (km/h - mph)	68 - 42	70 - 43	74 - 46	85 - 53	91 - 57
HULL STORAGE DIMENSIONS (METERS - FEET/INCHES)					
Length	4,46 - 14'8"	4,73 - 15'6"	5,71 - 18'9"	6,8 - 22'4"	7,78 - 25'6"
Width	1,53 - 5'0"	1,54 - 5'1"	1,57 - 5'2"	2,5 - 8'2"	2,26 - 7'5"
Height	1,42 - 4'8"	1,7 - 5'7"	1,7 - 5'7"	2,4 - 7'11"	2,2 - 7'3"
Hull angle	24,5°	24,5°	24°	25°	24°

All dimension measurements indicated have a tolerance of +/- 3%. Weight and speed measurements have a tolerance of +/- 5%.

(1) The maximum payload rating has been calculated according to ISO standards. Operating at or near maximum payloads is only advised in calm water and at reduced speeds.

(2) The spread of engine sizes corresponds to the efficient use of the boat with an average load. The minimum power is exploitable in relaxed activities, such as fishing, while the maximum recommended power is destined for performance activities such as water-skiing. For additional information all Zodiac boats from 10'2"/3.10 m to 13'9"/4.20 m can plane with 2 people on board (total load of 310 lbs/140 kg) using only a 6-8 Hp/5-6 kW outboard.

(3) Where the boat is fitted with an engine that exceeds Zodiac's maximum recommended power it must be treated with extreme care. This application is directed at experienced users using their boats for very specific purposes (carrying heavy loads, etc.). The capacity plate shows the maximum allowed power. In no case shall the boat be fitted with an engine that exceeds this power.

(4) Maximum authorized weight: Dry weight, according to engine manufacturers catalogue's specifications. Where the boat is fitted with an engine that exceeds Zodiac's maximum recommended power it must be treated with extreme care. This application is directed at experienced users using their boat for very specific purposes (carrying heavy loads, etc.). The capacity plate shows the maximum allowed power. In no case shall the boat be fitted with an engine that exceeds this power.

(5) Maximum speeds are given only as a general guide to understanding boat performance. They have been established by experienced professional pilots in ideal navigating conditions with one person aboard. Boat speed will be affected by the make of the motor, boat load, propeller and the water and weather conditions.

HULL

- Deep-V fibreglass hull (with built-in flaps on the Medline IIC)
- Moulded non-skid deck
- One bow D-ring
- Polyester bow roller (Medline III)
- Self draining deck when empty (Medline IIC), when loaded (Medline II)
- 1 anchor locker (except Medline Sundream)
- 1 bow locker (+ removable storage box 75 litres on Medline IV)
- 1 lateral locker (except Medline Sundream)
- 2 lateral lockers (Medline III / IV)
- 2 underdeck lockers (Medline Sundream)
- 1 rear locker (with compartments on Medline III)
- 3 mooring cleats (Medline IIC / II)
- 4 mooring cleats, 2 of which can be recessed in the rear (Medline III)
- 2 mooring cleats at the back, 1 front mooring bollard (Medline IV)
- Cup holders (Medline IIC / II / III / IV)
- Additional motor bracket for auxiliary engine fitting (Medline II)
- Stainless and teak rear platform (Medline II)
- Self-bailer :
 - 1 on Medline IIC
 - 2 on Medline Sundream / II
 - 2 high volume + 3 low volume self-bailers on Medline III
 - 4 high volume on Medline IV

BUOYANCY TUBE

- Removable tube system
- Sharc™ Duotex™ 2 x 1100 decitex fabric (Medline II / III / IV)
- Strongan™ Duotex™ 2 x 1100 decitex fabric (Medline Sundream / IIC)
- Semi-recessed valves
- 4 stainless steel grab handles (3 on Medline IIC / 6 on Medline IV)
- Polyester lashing on Medline Sundream
- Polyester bow roller (Medline Sundream / IIC / II / IV)
- Ultra large rubbing strake
- 6 exterior handles (4 on Medline Sundream)
- 2 interior handles (Medline IIC)
- 2 cleats (Medline IIC / II)
- Reinforced crowned cone ends

STANDARD EQUIPMENT ON MEDLINE SUNDREAM, IIC AND II

- Console with :
 - Wood steering wheel (except Medline Sundream)
 - + steering system
 - + steering cable (except Medline II)
 - Windscreen + stainless steel grab handle
 - 3 circuit breakers (except Medline Sundream) (7 on Medline IIC)
 - Glove box
 - Recess for fire extinguisher (except Medline Sundream)
- Pilot/co-pilot seat with collapsible back rest and removable upholstered cushions (fixed back rest on Medline Sundream)
- Passenger seat with upholstered cushion in front of the console
- Aft sundeck with upholstery (except Medline Sundream)
- Battery box (except Medline Sundream)
- Battery switch (except Medline Sundream)
- Bathing ladder
- Automatic bilge pump (except Medline Sundream)
- 2 paddles
- Foot pump
- 1 repair kit
- Owner's manual
- Valve cap pressure gauge

EQUIPMENT SPECIFIC TO MEDLINE SUNDREAM

- Built-in fuel tank (60 litres / 15.85 US gal) + gauge + fuel

EQUIPMENT SPECIFIC TO MEDLINE IIC

- Combined pilot seat/bolster
- Cup holders and 12V plug on console
- Built-in fuel tank (120 litres / 31.7 US gal) + gauge + fuel/ water separator + filter
- Anchor

EQUIPMENT SPECIFIC TO MEDLINE II

- Combined pilot seat/bolster
- Hydraulic steering
- Built-in fuel tank (220 litres / 58.1 US gal) + gauge + fuel/ water separator + filter
- Central stainless steel mast with water-skiing ring and white navigation lights

STANDARD EQUIPMENT ON MEDLINE III & IV

- Console complete with :
 - Complete hydraulic steering system (binnacle gas control not provided) and wooden wheel
 - "Bubble" windscreen
 - stainless steel grab handle
 - 3 circuit breakers (8 on Medline IV)
 - 2 x 12-volt plugs
 - Passenger handle
 - Glove box
 - 3 recessed cup holders
 - Footrest
 - Passenger seat with upholstered cushion at the front of the console
- Cabin with :
 - Door with portlight and lock
 - Electric lighting
 - Interior living space with full carpet doubling
 - Lockers
- Bolster :
 - Recess for fire extinguisher
 - Interior locker
- Central stainless steel mast with water-skiing ring and white navigation lights
- Telescopic fold down bathing ladder
- Shower kit + fresh water tank (50 litres / 13.2 US gal)
- Built-in fuel tanks (rear 176 litres / 46.5 US gal - bow 168 litres / 44.4 US gal) + gauge + fuel/water separator
- Deck lights
- Navigation lights
- 2 battery boxes
- 2 battery switches + 1 charge distributor
- 2 battery couplers
- 2 automatic bilge pumps
- 2 paddles
- 1 footpump
- 1 repair kit
- Owner's manual
- Valve cap pressure gauge

EQUIPMENT SPECIFIC TO MEDLINE III

- Fittings for electric windlass
- Forward picnic table + sundeck cushions
- Passenger seats with upholstery (3 seats)
- 2 Built-in fuel tanks (rear 176 litres / 46.5 US gal - bow 168 litres / 44.4 US gal) + gauge + fuel/ water separator + filter

EQUIPMENT SPECIFIC TO MEDLINE IV

- Front & back sundeck cushions
- Aft area : 4-seat bench, picnic table
- Built-in fuel tank (400 litres / 105.7 US gal) + gauge + fuel/water separator
- Synthetic teak deck

MAIN OPTIONAL ACCESSORIES

- Canvas hood
- 12-volt high pressure electric pump
- Overall cover
- Fore picnic table + sundeck (Medline Sundream / IIC / II)
- Roll-bar (Medline Sundream / IIC)
- Central stainless steel mast with water-skiing ring (Medline IIC)
- Synthetic teak deck (Medline IIC / II / III)
- Shower kit + fresh water tank (50 litres / 13.2 US gal) (Medline IIC / II)
- Auxiliary motor bracket (Medline II)
- Ski mast (Medline Sundream / IIC)
- Console cover (Medline III / IV)
- Bolster cover (Medline III / IV)
- Hob (Medline III / IV)
- Electric windlass (Medline III)
- Electrical cooler (Medline III / IV)
- Stereo sound system (Medline IV)
- Navigation lights (Medline Sundream / IIC)
- Bilge pump (Medline Sundream)

(6) Medline II: 11 passengers (category C), 5 passengers (category B).
 Medline III and Medline IV: 15 passengers (category C), 8 passengers (category B).
 N-Zo: 15 passengers (category C), 5 passengers (category B).
 Pro Open 650: 13 passengers (category C), 5 passengers (category B).
 Pro Open 850: 15 passengers (category C), 8 passengers (category B).
 Pro 15 Man: 15 passengers (category C), 5 passengers (category B).
 Pro 20 Man: 20 passengers (category C), 10 passengers (category B).

(7) Long shaft for twin engine installation.
 (8) 2 x 150 Hp / 113 kW for twin engine installation.
 (9) 2 x 225 kg / 496 lbs for twin engine installation.
 (10) 2 x 225 Hp / 168 kW for twin engine installation.
 (11) 2 x 272 kg / 600 lbs for twin engine installation.
 (12) Shaft XL for twin engine installation.